



Close this window

**Common Name:** CARPET EXTRACTION CLEANER

**Manufacturer:** 3M

**MSDS Revision Date:** 8/13/2001

**Grainger Item Number(s):** 3U166, 3VC55

**Manufacturer Model Number(s):** 9H, CARPET EXTRACTION CLNR

## MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

- [1. INGREDIENT](#)
- [2. PHYSICAL DATA](#)
- [3. FIRE AND EXPLOSION HAZARD DATA](#)
- [4. REACTIVITY DATA](#)
- [5. ENVIRONMENTAL INFORMATION](#)
- [6. SUGGESTED FIRST AID](#)
- [7. PRECAUTIONARY INFORMATION](#)
- [8. HEALTH HAZARD DATA](#)

### MATERIAL SAFETY DATA SHEET

3M  
3M CENTER  
ST. PAUL, MINNESOTA 55144-1000  
1-800-364-3577 OR (651) 737-6501 (24 HOURS)

COPYRIGHT, 2001, MINNESOTA MINING AND MANUFACTURING COMPANY. ALL RIGHTS RESERVED. COPYING AND/OR DOWNLOADING OF THIS INFORMATION FOR THE PURPOSE OF PROPERLY UTILIZING 3M PRODUCTS IS ALLOWED PROVIDED THAT:

1) THE INFORMATION IS COPIED IN FULL WITH NO CHANGES UNLESS PRIOR AGREEMENT IS OBTAINED FROM 3M, AND

2) NEITHER THE COPY NOR THE ORIGINAL IS RESOLD OR OTHERWISE DISTRIBUTED WITH THE INTENTION OF EARNING A PROFIT THEREON.

DIVISION: COMMERCIAL CARE DIVISION

TRADE NAME: 3M BRAND CARPET EXTRACTION CLEANER

ID NUMBER/U.P.C. :  
41-1500-1322-9  
61-5000-9485-1 00-48011-05719-9  
61-5001-1266-1 00-48011-18091-5

ISSUED: AUGUST 13, 2001

SUPERSEDES: MAY 25, 1999

DOCUMENT: 05-3149-1

## 1. INGREDIENT

| INGREDIENT                            | C.A.S. NO. | PERCENT |
|---------------------------------------|------------|---------|
| WATER                                 | 7732-18-5  | 60-90   |
| SODIUM TRIPOLYPHOSPHATE               | 7758-29-4  | 3-7     |
| POLYOXYETHYLENE MONOOCTYLPHENYL ETHER | 9036-19-5  | 3-7     |
| 2-BUTOXYETHANOL                       | 111-76-2   | 1-5     |
| SODIUM XYLENE SULFONATE               | 1300-72-7  | 1-5     |

IN CASE OF EMERGENCY:

THE NUMBERS AT THE BEGINNING OF THIS MSDS PROVIDE 24 HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT.

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL OR CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND 40 CFR PART 372:  
2-BUTOXYETHANOL

## 2. PHYSICAL DATA

BOILING POINT: 212 F

VAPOR PRESSURE: N/D

VAPOR DENSITY: 4.0 AIR = 1

EVAPORATION RATE: N/D

SOLUBILITY IN WATER: COMPLETE

SPECIFIC GRAVITY: CA. 1.04 WATER = 1

PERCENT VOLATILE: 80 - 90%

pH: 8.5

VISCOSITY: <100 CENTIPOISE

MELTING POINT: N/A

APPEARANCE AND ODOR:

LIQUID, COLORLESS TO LIGHT AMBER COLOR; PLEASANT FRAGRANCE

### 3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >200 F

FLAMMABLE LIMITS - LEL: N/D

FLAMMABLE LIMITS - UEL: N/D

AUTOIGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA: WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, FOAM

SPECIAL FIRE FIGHTING PROCEDURES:

WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET, SELF-CONTAINED, POSITIVE PRESSURE OR PRESSURE DEMAND BREATHING APPARATUS, BUNKER COAT AND PANTS, BANDS AROUND ARMS, WAIST AND LEGS, FACE MASK, AND PROTECTIVE COVERING FOR EXPOSED AREAS OF THE HEAD.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN.

NFPA HAZARD CODES:

|            |   |
|------------|---|
| HEALTH     | 2 |
| FIRE       | 0 |
| REACTIVITY | 0 |

UNUSUAL REACTION HAZARD: NONE

OSHA FIRE HAZARD CLASS: NOT APPLICABLE

### 4. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID: NONE KNOWN.

HAZARDOUS POLYMERIZATION: HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON MONOXIDE AND CARBON DIOXIDE, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS, IRRITANT VAPORS OR GASES.

### 5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

OBSERVE PRECAUTIONS FROM OTHER SECTIONS. VENTILATE AREA. CONTAIN SPILL. COVER WITH INORGANIC ABSORBENT MATERIAL. COLLECT SPILLED MATERIAL. CLEAN UP RESIDUE WITH WATER. PLACE IN A CLOSED CONTAINER.

RECOMMENDED DISPOSAL:

INCINERATE IN AN INDUSTRIAL OR COMMERCIAL FACILITY IN THE PRESENCE OF A COMBUSTIBLE MATERIAL.

ENVIRONMENTAL DATA: NOT DETERMINED.

## REGULATORY INFORMATION:

VOLATILE ORGANIC COMPOUNDS: CA. 27 GMS/LITER.  
VOC LESS H2O & EXEMPT SOLVENTS: N/D.

SINCE REGULATIONS VARY, CONSULT APPLICABLE REGULATIONS OR AUTHORITIES BEFORE DISPOSAL. IN THE EVENT OF AN UNCONTROLLED RELEASE OF THIS MATERIAL, THE USER SHOULD DETERMINE IF THE RELEASE QUALIFIES AS A REPORTABLE QUANTITY. U.S. EPA HAZARDOUS WASTE NUMBER = NONE (NOT U.S. EPA HAZARDOUS).

## TSCA:

ALL COMPONENTS USED IN THE MANUFACTURE OF THIS MATERIAL ARE IN COMPLIANCE WITH THE US TSCA INVENTORY.

## EPCRA HAZARD CLASS:

FIRE HAZARD: NO  
PRESSURE: NO  
REACTIVITY: NO  
ACUTE: YES  
CHRONIC: YES

## 6. SUGGESTED FIRST AID

## EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

## SKIN CONTACT:

FLUSH SKIN WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

## INHALATION:

IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN.

## IF SWALLOWED:

DO NOT INDUCE VOMITING. DRINK TWO GLASSES OF WATER. CALL A PHYSICIAN.

## 7. PRECAUTIONARY INFORMATION

EYE PROTECTION: AVOID EYE CONTACT.

SKIN PROTECTION: AVOID PROLONGED OR REPEATED SKIN CONTACT.

RECOMMENDED VENTILATION: USE WITH ADEQUATE DILUTION VENTILATION.

RESPIRATORY PROTECTION: AVOID PROLONGED BREATHING OF VAPORS.

## PREVENTION OF ACCIDENTAL INGESTION:

WASH HANDS AFTER HANDLING AND BEFORE EATING.

## RECOMMENDED STORAGE:

STORE IN A COOL PLACE. STORE AWAY FROM HEAT. KEEP CONTAINER IN WELL-VENTILATED AREA. KEEP OUT OF THE REACH OF CHILDREN.

FIRE AND EXPLOSION AVOIDANCE: KEEP CONTAINER TIGHTLY CLOSED.

| INGREDIENT                            | EXPOSURE LIMITS |              |      | AUTH  | SKIN* |
|---------------------------------------|-----------------|--------------|------|-------|-------|
|                                       | VALUE           | UNIT         | TYPE |       |       |
| WATER                                 | NONE            | NONE         | NONE | NONE  |       |
| SODIUM TRIPOLYPHOSPHATE               | NONE            | NONE         | NONE | NONE  |       |
| POLYOXYETHYLENE MONOOCTYLPHENYL ETHER | NONE            | NONE         | NONE | NONE  |       |
| 2-BUTOXYETHANOL                       | 25              | PPM          | TWA  | ACGIH | Y     |
| 2-BUTOXYETHANOL                       | 25              | PPM          | TWA  | OSHAV | Y     |
|                                       |                 | OSHA VACATED | PEL  |       |       |
| 2-BUTOXYETHANOL                       | 50              | PPM          | TWA  | OSHA  | Y     |
| SODIUM XYLENE SULFONATE               | NONE            | NONE         | NONE | NONE  |       |

\* SKIN NOTATION:

LISTED SUBSTANCES INDICATED WITH 'Y' UNDER SKIN REFER TO THE POTENTIAL CONTRIBUTION TO THE OVERALL EXPOSURE BY THE CUTANEOUS ROUTE INCLUDING MUCOUS MEMBRANE AND EYE, EITHER BY AIRBORNE OR, MORE PARTICULARLY, BY DIRECT CONTACT WITH THE SUBSTANCE. VEHICLES CAN ALTER SKIN ABSORPTION.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

OSHAV:

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION VACATED PEL. VACATED PERMISSIBLE EXPOSURE LIMITS (PEL) ARE ENFORCED AS THE OSHA PEL IN SOME STATES. CHECK WITH YOUR LOCAL REGULATORY AUTHORITY.

NONE: NONE ESTABLISHED

## 8. HEALTH HAZARD DATA

EYE CONTACT:

MODERATE EYE IRRITATION:

SIGNS/SYMPTOMS CAN INCLUDE REDNESS, SWELLING, PAIN, TEARING, AND HAZY VISION.

SKIN CONTACT:

MILD SKIN IRRITATION (AFTER PROLONGED OR REPEATED CONTACT):

SIGNS/SYMPTOMS CAN INCLUDE REDNESS, SWELLING, AND ITCHING.

MAY BE ABSORBED THROUGH THE SKIN AND PRODUCE EFFECTS SIMILAR TO THOSE CAUSED BY INHALATION AND/OR INGESTION.

INHALATION:

SINGLE OVEREXPOSURE, ABOVE RECOMMENDED GUIDELINES, MAY CAUSE:

IRRITATION (UPPER RESPIRATORY):

SIGNS/SYMPTOMS CAN INCLUDE SORENESS OF THE NOSE AND THROAT, COUGHING AND SNEEZING.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

SINGLE OVEREXPOSURE, ABOVE RECOMMENDED GUIDELINES, MAY CAUSE:

CENTRAL NERVOUS SYSTEM DEPRESSION:

SIGNS/SYMPTOMS CAN INCLUDE HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS AND UNCONSCIOUSNESS.

IF SWALLOWED: INGESTION IS NOT A LIKELY ROUTE OF EXPOSURE TO THIS PRODUCT.

INGESTION MAY CAUSE:

GASTROINTESTINAL EFFECTS:

SIGNS/SYMPTOMS GENERALLY WILL INCLUDE ABDOMINAL PAIN.

SECTION CHANGE DATES:

| HEADING | SECTION CHANGED SINCE MAY 25, 1999 | ISSUE |
|---------|------------------------------------|-------|
|---------|------------------------------------|-------|

THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET (MSDS) IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. USER IS RESPONSIBLE FOR DETERMINING WHETHER THE 3M PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION. GIVEN THE VARIETY OF FACTORS THAT CAN AFFECT THE USE AND APPLICATION OF A 3M PRODUCT, SOME OF WHICH ARE UNIQUELY WITHIN THE USER'S KNOWLEDGE AND CONTROL, IT IS ESSENTIAL THAT THE USER EVALUATE THE 3M PRODUCT TO DETERMINE WHETHER IT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION.

3M PROVIDES INFORMATION IN ELECTRONIC FORM AS A SERVICE TO ITS CUSTOMERS. DUE TO THE REMOTE POSSIBILITY THAT ELECTRONIC TRANSFER MAY HAVE RESULTED IN ERRORS, OMISSIONS OR ALTERATIONS IN THIS INFORMATION, 3M MAKES NO REPRESENTATIONS AS TO ITS COMPLETENESS OR ACCURACY. IN ADDITION, INFORMATION OBTAINED FROM A DATABASE MAY NOT BE AS CURRENT AS THE INFORMATION IN THE MSDS AVAILABLE DIRECTLY FROM 3M.

ABBREVIATIONS:

N/D - NOT DETERMINED

N/A - NOT APPLICABLE

CA - APPROXIMATELY